

APREAMARE GOZZO 35

1 ENGINES

2 * VOLVOPENTA D4-270 DPI 270mhp-199 kW at 3500 rpm 2*VOLVOPENTA D4-320 SHAFT DRIVE 320mhp-235 kW at 3600 rpm

2 SPEED (knots)			
Martin and Latin Principal Principal	VP D4 270 DPI		VP D4 320 SHAFT
Maximum speed at medium load displacement	33	knots	31
Cruising speed at medium load displacement	28	knots	26
3 RANGE (nautical miles)			
	VP D4 270 DPI		VP D4 320 SHAFT
Maximum speed	228	n.m.	160
Cruising speed	243	n.m.	228
4 MAIN SIZES			
Loa = overall length (standard ISO 8666)	11,20	m.	36 ft. 9 in.
Lh = Hull length (standard ISO 8666)	9,95	m.	32 ft. 8 in.
Lg = waterline length (boat fully laden)	9,64	m.	31 ft. 8 in.
Max. beam	3,70	m.	12 ft. 2 in.
Depth under propellers (boat fully laden)	0,90	m.	2 ft. 11 in.
Displacement unladen	7,0	ton./lb.	15432
Displacement laden	9,0	ton./lb.	19842
Max.number of persons on board	14		
Navigation category CE 2003/44	В		
Certification modules	A1		R.I.Na.
5 TECHNICAL DATA			
Hull type : deadrise . Warped hull with spray rails			
H t = Minimum transport height under propellers	3,95	m.	12 ft. 11 in.
Fuel tank capacity	700	It./US gals.	. 185
Fresh water tank capacity	170	It./US gals.	45
Black water tank capacity	50	It./US gals.	. 13

Technical data, performance and range figures, designs and graphic reproductions contained herein have no certification value. They are purely descriptive and refer to standard models. Actual technical or descriptive specifications must be provided solely with regards to the craft being purchased. Therefore, any indications will be binding for the seller only if contained in the sales contract and in the relevant manual